

Uncontrolled document as of January 10, 2009. Refer to website for up to date specifications.

CASES 1300 Case



1300 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

1300 Case Configurations

Cat. #	Description
1300	1300 Case
1300NF	1300 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1300 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
10.62" x 9.68" x 6.87" (27 x 24.6 x 17.4 cm)		9.87" x 7.00" x 6.12" (25.1 x 17.8 x 15.5 cm)	
Lid Depth	Bottom Depth	Total Depth	
1.18" (3 cm)	4.93" (12.5 cm)	6.11" (15.5 cm)	
Weight with Foam	Weight without Foam	Buoyancy Max.	
3.53 lbs. (1.6 kg)	3.09 lbs. (1.4 kg)	12.35 lbs. (5.6 kg)	

Range Temperature

-40 / 210° F
 (-40 / 99° C)

1300 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1300 Case Accessories

Cat. #	Description
1200PF	Special Application Panel Frame
1203	Replacement O-ring
1301	4 pc. Replacement Foam Set
1400IP	Instapak Quick® RT