

Uncontrolled document as of January 10, 2009. Refer to website for up to date specifications.

CASES 1600 Case



1600 Case

- **Watertight, crushproof, and dust proof**
- Open cell core with solid wall design - strong, light weight
- Automatic Pressure Equalization Valve
- O-ring seal
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

1600 Case Configurations

Cat. #	Description
1600	1600 Case
1600NF	1600 Case (No foam)
1604	1600 Case with Padded Dividers



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1600 Case Specifications

Exterior Dimensions (L x W x D) 24.25" x 19.43" x 8.68" (61.6 x 49.3 x 22 cm)	Interior Dimensions (L x W x D) 21.43" x 16.50" x 7.87" (54.4 x 41.9 x 20 cm)	
Lid Depth 1.75" (4.4 cm)	Bottom Depth 6.12" (15.5 cm)	Total Depth 7.87" (20 cm)
Weight with Foam 14.11 lbs. (6.4 kg)	Weight without Foam 13 lbs. (5.9 kg)	Buoyancy Max. 74.96 lbs. (34 kg)

Range Temperature

-40 / 210° F
 (-40 / 99° C)

Personalized Nameplate Available

1600 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1600 Case Accessories

Cat. #	Description
1600IP	Instapak Quick® RT
1601	4 pc. Replacement Foam Set
1602	Pick 'N' Pluck™ Sections Only (set of 2)
1603	Replacement O-ring
1605	Padded Divider Set Only
1609	Lid Organizer