

Uncontrolled document as of January 11, 2009. Refer to website for up to date specifications.

**LIGHTS**  
**1800**  
 PeliLite



**PeliLite™ 1800 Flashlight**

This one is built to last. The unbreakable ABS body resists chemicals, water and corrosion. The polycarbonate lens and focused Xenon lamp module produce a tight white beam that penetrates smoke and fog. The PeliLite 1800 flashlight is submersible, thanks to the o-ring seal and twist-on shroud that eliminates leaky switches. It is powered by 2 C alkaline cells.

Minimum Pack 6 ea.  
 Packaged Weight: 3.8 oz.



**NSN List**

NSN #	Description
6230-01-365-7648	1800 Orange
6230-01-465-5045	1800C Black

**PeliLite™ 1800 Flashlight Configurations**

Cat. #	Description
1800	PeliLite™ 1800 Flashlight (Carded)



**PeliLite™ 1800 Flashlight Specifications**

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
Xenon	15.0	5300

  

Batteries	Battery Burn Time	Battery Pack/Charging Time
2 C Alkaline (Not included)	8 hrs.	N/A

  

Watts	Voltage
2.2	3

  

Length	Weight w/Batteries	Weight w/o Batteries
6" (15.2 cm)	7.8 oz. (0.22 kg)	2.9 oz. (0.08 kg)

**PeliLite™ 1800 Flashlight Approvals**

	Class I, Div. 2; Gp ABCD, T3C / Class II; Div. 2; Gp G.
	Class I, Div. 2; Gp. ABCD / Class II; Div. 2; Gp. G; T4
	Listed 4S67/E184884 Class I, Div. 2; Gp. D / Class I; Zone 2; Gp. IIA; T3
	10C-628-0

**PeliLite™ 1800 Flashlight Accessories**

Cat. #	Description
1804	PeliLite™ 1800 Xenon Lamp Module