

Uncontrolled document as of January 11, 2009. Refer to website for up to date specifications.

LIGHTS
1820
Pocket Sabre



Pocket Sabre™ 1820 Flashlight

The Pocket Sabre 1820 flashlight descended from Pelican's famous SabreLite 2000. Built to last, the unbreakable ABS body resists chemicals, water and corrosion. The polycarbonate lens and focused Xenon lamp module produce a tight white beam that penetrates any hazardous condition. All these features and safety approvals, too. It comes with a twist-on shroud, is submersible, and powered by 2 C alkaline cells.

Minimum Pack 6 ea.
 Packaged Weight: 9.4 oz.



Submersible

NSN List

NSN #	Description
6230-01-297-5080	1820B Black

Pocket Sabre™ 1820 Flashlight Configurations

Cat. #	Description
1820	Pocket Sabre™ 1820 Flashlight (Carded)



Pocket Sabre™ 1820 Flashlight Specifications




Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
Xenon	15.0	5300

Batteries	Battery Burn Time	Battery Pack/Charging Time
2 C Alkaline (Included in select packaging)	8 hrs.	N/A

Watts	Voltage
2.2	3

Length	Weight w/Batteries	Weight w/o Batteries
5.83" (14.8 cm)	8.3 oz. (0.24 kg)	3.3 oz. (0.09 kg)

Pocket Sabre™ 1820 Flashlight Approvals

	Class I, Div. 2; Gp ABCD, T4; Class II, III, Div. 2; Gp FG -35° +40°C.
	Class I, Div. 2; Gp. ABCD; T4 / Class II, III, Div. 2; Gp. FG.
	Listed 4S67/E184884 Class I, Div. 2 Gps.D, T2D.
IECEx	Ex ib e IIC T3 IP67 IEC Ex TSA 06.0021X

Pocket Sabre™ 1820 Flashlight Accessories

Cat. #	Description
1804	Pocket Sabre™ 1820 Lamp Module

